


EB-G6270W



DATASHEET



The EB-G6270W is a professional installation projector ideal for corporate environments, education applications, rental markets and digital signage. Important presentations and sales campaigns are delivered with rich, vivid colours - even in daylight, thanks to Epson's 3LCD technology and equally high White and Colour Light Output. The projector can even be placed in difficult positions thanks to a number of innovative installation features.

Ensure superb quality and the best possible delivery of presentations with the EB-G6270W. This 6,500-lumen projector includes Epson's 3LCD technology and high brightness to display images with more accurate colours and clearer detail. A new enhanced standard lens helps reduce flare and improve focus.

Set-up and installation is simple and straightforward. A wide lens shift allows easy placement of the projector, even in difficult positions, without distorting or blurring the image. In addition, a powerful zoom lens, as well as manual vertical keystone correction and centred lens, make it even easier to set-up in various positions. The projector can also be rotated vertically by 360 degrees allowing images to be projected directly onto the ceiling and the floor¹.

KEY FEATURES

- **Ultra-bright output**
Equally high 6,500lm White and Colour Light Output
- **High-quality image**
3LCD technology, WCLO, colour uniformity, enhanced standard lens
- **Flexible installation**
Wide lens shift, manual vertical keystone correction
- **Easy to set up**
HDBaseT and HDMI connectivity.
Compatible with Epson EB-G5 series lenses²



EPSON
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.76 inch with C2 Fine
IMAGE	
Colour Light Output	6,500 lumen-4,550 lumen (economy)
White Light Output	6,500 lumen - 4,550 lumen (economy)
Resolution	WXGA, 1280 x 800, 16:10
Contrast Ratio	5,000 : 1
Lamp	380 W, 2,000 h durability, 4,000 h durability (economy mode)
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °
High Definition	HD ready
Aspect Ratio	16:10
Colour Processing	10 Bits
OPTICAL	
Projection Ratio	1.26 - 2.30:1
Zoom	Manual, Factor: 1 - 1.8
Projection Size	50 inches - 300 inches
Projection Distance Wide	1.4 m - 8.4 m
Projection Distance Tele	2.5 m - 15 m
Projection Lens F Number	1.65 - 2.55
Focal Distance	21.28 mm - 37.94 mm
Focus	Manual
Projection Lens Zoom Ratio	1 - 1.8 : 1
Lens	Optical
Lens Shift	Manual - Vertical ± 67 %, horizontal ± 30 %
CONNECTIVITY	
Interfaces	HDBaseT, Cinch audio in, RS-232C, Stereo mini jack audio in (4x), Stereo mini jack audio out, S-Video in, BNC in, Composite in, Display Port, HDMI in, VGA out, VGA in, Wireless LAN IEEE 802.11b/g/n (optional), WLAN, 10 Base-T, Ethernet interface (100 Base-TX / 10 Base-T)
ADVANCED FEATURES	
Security	Kensington lock, Password lock
Features	Mute key, Network administration, Network image transmission, PC Free, Quick Corner, Six axis color control, Split-Screen-Function, Transport handle
Video Colour Modes	Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM
2D Colour Modes	Auto, Dynamic, Living room, Natural, Cinema
GENERAL	
Energy Use	542 W, 405 W (economy), 0.41 W (standby)
Product dimensions	505 x 406 x 171 mm (Width x Depth x Height)
Product weight	9.9 kg
Noise Level	Normal: 39 dB (A) - Economy: 31 dB (A)
Included Software	EasyMP Monitor, EasyMP Multi PC Projection
Loudspeaker	10 W
Supply Voltage	AC 100 V - 240 V,50 Hz - 60 Hz
Temperature	Storage -10° C - 60° C
Humidity	Operation 20% - 80%, Storage 10% - 90%
Options	MB22 ceiling mount
Sound Pressure	Operation: 39 dB (A)-standby: 31 dB (A)
OTHER	
Warranty	36 months On site service or 15,000 h, Lamp: 36 months or 1,000 h Optional warranty extension available

EB-G6270W

WHAT'S IN THE BOX

- Cable hook
- User manual (CD)
- Remote control incl. batteries
- Power cable
- Computer cable
- Cable cover

1. - Requires additional ceiling mount 2 - Except ELPLS05 lens



OPTIONAL ACCESSORIES

- 3D Polarizer - ELPPL01
V12H618A01
- Air Filter - ELPAF43
V13H134A43
- Lamp - ELPLP76
V13H010L76
- Quick Wireless Connect USB key - ELPAP09
V12H005M09
- Wireless LAN Adapter (b/g/n) - ELPAP07
V12H418P13
- Ceiling Mount (White) - ELPMB22
V12H003B22

OPTIONAL LENSES

- Lens (ST Off Axis) - ELPLU01
V12H004U01
- Lens (Long Throw) - ELPLL06
V12H004L06
- Lens (Middle Throw 2) - ELPLM05
V12H004M05
- Lens (Middle Throw 1) - ELPLM04
V12H004M04
- Lens (Rear Wide) - ELPLR03
V12H004R03

LOGISTICS INFORMATION

SKU	V11H702041
EAN code	8715946548579
Dimensions Single Carton	762 x 432 x 324 mm
Carton Weight	12.9 Kg
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	7 Units
Pallet Size Block	7 Units



For more information please contact:

Telephone: 01952 607111 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740
+ Local call rate.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON®